

HFSAB

H. FOLKE SANDELIN AB

CABLE STRIPPING MACHINE - MODEL SM-H



WORLD LEADING SUPPLIER TO THE CABLE INDUSTRY

HFSAB

H. FOLKE SANDELIN AB

- Remove an outer jacket of PE, PVC, HDPE, etc without any damage to the cable layer below it, thus enabling the outer jacket to be re-applied and the cable repaired.
- Remove the lead sheath of the cable without damaging the moisture expansion tapes or any other kind of cable layer below it, thus allow the re-application of the lead sheath.
- Remove the triple XLPE insulation from the conductor core without damage to the expensive cable core and thus allow the conductor to be re-used, or sold at a higher value as bright copper scrap.
- Jointly or Individually adjustable slitting-knife depth.
- Normally no additional pulling equipment required.

TECHNICAL DATA

OPERATING SPEED 0-45 m/min

CABLE DIAMETER RANGE 10-125 mm

PRODUCTION DATA

OUTER SHEATH MATERIALS

PVC, PE, HDPE

MAX THICKNESS 5 mm

MIN THICKNESS 1 mm

LEAD SHEATH

MAX THICKNESS 5 mm

MIN THICKNESS 1 mm

INSULATION (round constructions only)

MAX THICKNESS 15 mm

MIN THICKNESS 2 mm



H. Folke Sandelin AB
Dynamovägen 7
Box 4086
SE-591 04 Motala
Sweden

Tel. +46 (0) 141 20 36 30
Fax. +46 (0) 141 20 36 39
E-mail. hfsab@hfsab.com
Web. www.hfsab.com



CABLE ENTRY



DRIVEN ROLLERS



UNDAMAGED CORE AFTER SLITTING



REMOVED MATERIAL